

WARRANTY

FIW Steel Sdn. Bhd. (Manufacturer of ColourMaxx® Prisma), warrants to _____ that the ColourMaxx® Prisma steel if correctly installed and maintained on the _____ project at _____.

- Shall not perforate by corrosion for : 10 Years*
- Shall not peel, fade and chalk excessively for : 5 Years*

*Terms and conditions apply. Please consult FIW Steel Sdn. Bhd. representative

If the ColourMaxx® Prisma steel roofing/cladding/flashing (installed and maintained in accordance with the specific guidelines, terms and conditions on the reverse) fails to perform as warranted due to a defect in the material, the roofing will be repaired or resupplied, or compensation provided with due regard to the pro-rata of actual performance versus warranted performance. No liability shall be accepted for any consequential loss or damages attributable to the failure.

This is to certify that representatives or agent of FIW Steel Sdn. Bhd. have inspected the installed roofing, and ascertained (by best endeavours) that

- The roofing/cladding/flashing is manufactured from prime quality ColourMaxx® Prisma
- The roofing/cladding/flashing appears to have been properly installed (or any concerns are noted below); and
- The environment in or around structure does not appear to be abnormally or severely corrosive

Warranty No. : Installation Date :
Inspected By : Date :
Inspected By : Date :
Material Used :
Delivery Order No. :
D/O Date :
Coil Weight :

Authorised by : _____ Date : _____
FIW Steel Sdn. Bhd.

Acknowledged by : _____ Date : _____

NOTE: This warranty is provided to, and can only be actioned by (roll former), subject to the expressed terms and conditions listed on the reverse. Failure, despite best endeavors, to identify problems with environment and/or installation during project inspection shall not preclude or limit the operation of the terms and conditions on the reverse.

TERMS AND CONDITIONS

This warranty is your assurance that **ColourMaxx® Prisma**, if properly installed and maintained, will meet minimum expected performance levels for at least the warranted period (commencing from the date of installation).

However, certain specific problems and situations (listed below) must be addressed and rectified early in order to get the best possible performance and, if not rectified, may result in the warranty being void.

1. The warranty applies only to roofing, cladding and flashing made from prime quality **ColourMaxx® Prisma**. Guttering, downpipes, brackets, doors and other accessories are excluded.
2. Roofing, cladding and flashing must be handled and installed in accordance with published FIW guidelines current at the time of installation, with particular attention to the issues listed below:-
 - a. Keep sheet dry at all times while stacked in bundles prior to installation. Wet sheet should be separated and dried to minimise risk of accelerated corrosion due to “wet stacking”.
 - b. Do not cut sheet by circular saw or grinders as high temperature swarf will damage the coating.
 - c. During construction, remove iron filling and/or steel debris arising from cutting, piercing with friction saws, abrasive discs or drills and other metal scraps such as rivet shanks, nails, screws and nuts immediately to minimise risk of localised corrosion.
 - d. The product is recommended to be used within 6 months after delivery date to minimize effect of aging phenomenon.
3. Fasteners must comply with AS 3566 Class 3 or Class 4, and be certified as such by the supplier of fasteners.
4. All fixings, flashings and associated components must be manufactured from compatible metals (**ColourMaxx® Alpha** steel, **GalMaxx® Alpha** steel, **Colourmaxx®** steel, **Galmass®** steel, zinc or aluminium) or be coated or plated in accordance with current published FIW guidelines. For long lasting consistency in appearance, flashings should be made from the same material as the cladding.
5. The paint finish as supplied must not be scratched, abraded, damaged, or coated with any foreign matter or incompatible material (including stack and flue deposits).
6. Product failures wholly or in part due to the following causes are **NOT** covered by this warranty:
 - a. Mechanical, chemical or other damage before, during or after installation.
 - b. Attack from chemical agents, fumes, liquids or solids other than direct rainfall.
 - c. Unwashed areas sheltered from normal rainfall and not regularly cleaned.
 - d. Extended contact with soil, dust, ashes, fertilizers, or moisture retaining substances.
 - e. Areas in metallic contact with incompatible materials (eg: lead, copper, carbon/graphite, or stainless steel) or subject to water run-off from such incompatible materials.
 - f. Failure to remove debris and/or failure to provide free drainage of water including internal condensation from all surfaces of the product.
 - g. Deterioration of the panels caused by contact with wet, green or treated timber.
 - h. Blistering or paint delamination caused by wet staking due to improper or long storage at job site.
 - i. Severe marine, industrial or corrosive environments unless specifically agreed and noted.
 - j. Storm and tempest or other Acts of God.
7. Failure of the product from corrosion is defined as when the sheet is perforated. Surface rust or minor corrosion at tension bends or cut edges due to natural weathering does not constitute failure of the product.

FIW Steel Sdn. Bhd.

No. 3, Jalan Keluli Satu, Kawasan Perindustrian Bukit Raja Selatan,
40000 Shah Alam, Selangor Darul Ehsan, Malaysia.

GalMaxx® and ColourMaxx® are registered trade mark of FIW Steel Sdn. Bhd.